



BatPac™CWS

BATPACCWS™ 31/54W COLOUR AND WATTAGE SWITCHABLE LED IK08 1500MM BATTEN 3000/4000/6500K

- Colour & Wattage Switchable high-efficiency (150lm/W) LED Battens with opal diffuser for even and uniform light distribution.
- Modular plug and play solution allows simple product extension on construction site by installing Microwave Sensor and/or Emergency Selftest Modules.
- Integrated flicker-free non-dimmable driver with loop in loop out connector for simplified and fast installation, knockouts on both ends for cable entry.
- 2 Wattage and 3 Colour Selections available for ultimate flexibility in every application and perfect retrofit solution for single and twin fluorescent fittings.
- Options: Microwave Sensor with 108° detection beam and range up to 4 meters. Emergency Pack 2.5W with Selftest function.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
CL149918	Non-Dimmable	3000 / 4000 / 6500K	31 / 54W	4350-7850lm	Up to 150lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

BatPacCWS™

BATPACCWS™ 31/54W COLOUR AND WATTAGE SWITCHABLE LED IK08 1500MM BATTEN 3000/4000/6500K

Specifications and Benefits

Ingress Protection Rating	IP20
IK Rating	IK08
Operating Temperature Range	-20°C / +45°C
Mounting Type	Surface mounted
Positional Adjustment	Fixed
Certification	CE
Protection Class	Class I
Body Material	Plastic
Cover Material	PC
Finishing	White
Available accessories	<ul style="list-style-type: none"> ·EM157449 Emergency Pack 2.5W Constant Wattage Selftest ·CL151300 Microwave Sensor Pack

Photometric Specifications

Lumens	31W - 4350 / 4650 / 4350lm
	54W - 7250 / 7850 / 7250lm
Efficiency	Up to 150lm/W
Colour Temperature	3000 / 4000 / 6500K
Light Colour Definition	Switchable White
SDCM	<6
Beam Angle	120°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Technical Specifications

Wattage	31 / 54W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.9
Switching Cycles	>30,000
Lifetime Hours	L70 B50 50,000hrs L80 B20 50,000hrs
Energy Rating	D
Insulation Coverable	N/A
Inrush Current	12A

Logistic Details

EAN / Barcode	3609640149918
Product Weight	1600g
Product Dimensions (ODxH / LxWxH)	1470 x 61 x 71mm
Boxed Product Weight	1860g
Boxed Product Dimensions (LxWxH)	1475 x 65 x 75mm
Outer Carton Boxed Product Quantity	8 pcs
Outer Carton Dimensions (LxWxH)	1490 x 285 x 165mm

